

Anchor Head Technical Data

Anchor Head Dimensions

Diameter	Thickness	Bearing Plate Thru Hole	Trumpet Size Required (Min.)
5"	2"	3-1/2"	3 - 1/2" SCH40
5-1/2"	2"	4"	4" SCH40
6-1/4"	2-5/8"	4-3/4"	5" SCH40
7-1/2"	2-3/4"	5"	5" SCH40
8-1/2"	3-1/2"	6"	6" SCH40
	5" 5-1/2" 6-1/4" 7-1/2"	5" 2" 5-1/2" 2" 6-1/4" 2-5/8" 7-1/2" 2-3/4"	Diameter Thickness Thru Hole 5" 2" 3-1/2" 5-1/2" 2" 4" 6-1/4" 2-5/8" 4-3/4" 7-1/2" 2-3/4" 5"

Any variation of custom sizes or machining such as external threading available upon request

Or HSS Equivalent



9 Strand Anchor Head



Anchor Head Side View



Accessories



Adjustable Stressing Chairs - available in 4, 7, 9, 12 and 15 Strand sizes.



Anchor Heads - Many standard sizes available as well as any custom anchor head if required.



Restrainer Plates - Standard restraining plates are kept in stock in the 4, 7, 9, 12, and 15 strand sizes however, any other size can be fabricated to match the required anchor.



Organizers - Can be made to accommodate any size of anchor.



Accessories



Grippers - Designed to be used with standard .600" 7 wire strand anchor tendon. Variety of sizes are available.



Cover Caps - Standard sizes stocked for 4, 7, 9, 12, and 15 strand anchor heads. Custom sizes are available.



Post Grout Tubes - any required length can be accommodated thanks to our modular system.



Centralizers - Various sizes and styles including balloon, snap ring, banana peel style, and heavy duty.



Couplers - designed to be used with standard 0.600" diameter, 7 wire anchor tendon.



Bearing Plates - any size or configuration can be accommodated including addition of trumpets if needed.